

## **3-BOARD TUBE TOP UTILITY**



## **3-BOARD TUBE TOP STANDARD FEATURES**

Angle Frame and Crossmembers Channel Tongue 2" x 1-1/2" Tube Uprights, 3 Treated Boards High 2" x 2" Square Tube Top Rail Posi-Lock Coupler with Safety Chains Enclosed Sealed Wiring Harness Top Wind Swivel Jack with Foot 50" Spring Assisted Gate and Grab Handle Steel Fenders with Backs Leaf Spring Suspension Easy Lube Hubs Radial Tires on White Steel Wheels Powder Coat Finish 2" Treated Lumber Decking Welded Front Board Retainer and Rear End Cap D-rings Spare Tire Carrier Full LED, DOT Compliant Lighting

## **SPECIFICATIONS**

	60" x 8' SA	60" x 10' SA	76" x 10' SA	76" x 12' SA	82" x 12' SA	82" x 14' SA
GAWR (Ibs/axle)	3500	3500	3500	3500	3500	3500
GVWR (Ibs)	2990	2900	2990	2990	2990	2990
Curb Weight (lbs)	945	1070	1140	1250	1290	1400
Load Capacity (lbs)	2045	1830	1850	1740	1700	1590
Main Frame	3" x 2" x 3/16" Steel Angle					
Crossmembers	3" x 2" x 3/16" Steel Angle					
Top Rail	2" x 2" Steel Tube					
Uprights	2" x 1-1/2" Steel Tube, 3 Board Treated Pine					
Tongue	3" Steel Channel					
Coupler	2" A-Frame					
Jack	2K Rated, Top Wind Swivel					
Axle	(1) 3500 lb Idler Easy Lube Hubs					
Suspension	Leaf Spring					
Tires	ST205-75R-15" 6-PR					
Wheels	15", 5-Hole					
Lights	LED					
Electric Plug	4-Prong Flat					
Decking	2" Treated Lumber					
Finish	Power Coat High Gloss Black					
Gate Style	Spring Assist Gate					
Gate Height	50"	50"	50"	50"	50"	50"
Gate Width	56"	56"	72"	72"	78"	78"
Overall Length	12'-2"	14'-2"	14'-2"	16'-2"	16'-2"	18'-2"
Overall Width	80 1/2"	80 1/2"	94 1/2"	94 1/2"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Length	8'-2"	10'-2"	10'-2"	12'-2"	12'-2"	14'-2"
Deck Width (Between Fenders)	60 1/4"	60 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

